mini-2x-vR-Cam
Technical specifications

Parameters	mini-2x-vR-Cam-zoom	mini-2x-vR-Cam-wide
Video output		
Ethernet	1	
Control Interface		
Ethernet	10/100 Mbit (RJ-45)	
Light Sensitive Matrix		
	1/1.8" SONY IMX385 CMOS	
Zoom Ratio		
	Optical x18	Optical x3
Resolution		
	1920×1080 59.94i, 1920×1080 29.97PsF, 1280×720 59.94p, 1920×1080 50p, 1920×1080 59.94p, 1920×1080 60p,	1920×1080 50i, 1920×1080 25PsF, 1280×720 50p 1920×1080 119.88p, 1920×1080 100p
Video format		
	PAL / NTSC	
Scanning System		
	Progressive, Interlace	
Signal/noise ratio		
	More than 50 dB (AGC Off)	
Minimum Illumination		
	Color: 0.5 lux, BW: 0.1lux, Color DSS: 0.125 lux, BW DSS: 0.025 lux	
Electronic Shutter Speed		
	Auto / Manual	
Temperature		
Operating / Storage	-20 °C to +60 °C (-4°F to 140°F) at humidity less than 90%	
Humidity		
Operating / Storage	0% to 90%	
Power		
Interface	Ethernet – PoE (RJ-45)	
Power consumption	less than 15 W	
Physical Parameters		
Dimensions	175 mm × 67 mm × 63 mm	149 mm × 54 mm × 54 mm
Weight	0,69 kg	0,42 kg

© Slomo.tv Inc., 2005 – 2026