

Options Simple R Series

Option	Description	Simple R		
		II	IIM	III
Transfer	Ability to transfer any clip or playlist to network integrated servers with the same option.	Included	Included	Included
Game Analyzer	Telestrator for imposition of graphical elements (line, arrow, curved arrow, circle, etc.) and free hand drawing on live video. Best with Wacom Cintiq tablet (not included).	Included	Included	Included
Upgrade 442 to 662	Upgrade from 4 Rec+4 Search+2 Play + FX to 6 Rec+ 6 Search+2 Play + FX.	✓	✓	✗ Basic 662
3G SDI support	Allows each SDI I/O to be used in 3G-SDI mode for 1080p50/60 and 1080i100/200 production.	✓	✓	✓
DMR™	Multi-Channel Recording direct in NLE native file format with DVCPPro/ProRes/DNxHD codecs. Support of XDCAM50/XAVC100 export. Includes 1U external Rack for four (4) 3.5" SATA hard drives.	✗	✓	✓
SDX*	8-slot High speed USB 3.0 SD card reader. SD cards are used for export/import of materials.	✗	✓	✓
2nd workplace	Additional replay operator's work place, including remote controller. It allows usage of the server as two undependable 662 replay machines.	✗	✗	✓
Built-in SSD storage expansion	Storage upgrade to 133/266/400 hrs. 100mbit.	✓	✓	✓
Redundant Power*	Dual mini redundant Power Supply.	✓	✓	✓
Export	MXF/QT Export of recorded material in native Apple Final Cut, Avid MC and Adobe Premiere files with DVCPPro /ProRes/DNxHD/AVC-Intra/XDCAM422 codecs.	✓	✓	✓
Super Motion	Support for High Speed Super Motion Cameras. (Requires 3 dedicated input channels).	✓	✓	✓

Option	Description	Simple R		
		II	IIM	III
Xtra Motion	Support for 6x GVG LDX-86 HS/XS camera (Requires 3 dedicated 3G SDI inputs) in 180p/360i mode.	✓ (Requires 3G)	✓ (Requires 3G)	✓ (Requires 3G)
HyperMotion	Support for 1000FPS Ikegami HiMotion-II camera (Requires from 1 to 3 dedicated SDI inputs). Includes Special HiMotion-II camera Remote cable.	✓	✓	✓
Panasonic Super Motion	Support of 4x Panasonic AK-HC5000 and 2x, 3x, 4x Panasonic AK-UC4000 Super Motion Cameras.	✓ (Requires 3G)	✓ (Requires 3G)	✓ (Requires 3G)
Safeguard	8 channels Full HD loop recording. In case of problems with the main recording unit desired video-material can be simply exported via Network or USB 3.0 ports.	✓ (For 662 model)	✓ (For 662 model)	✓
8-channel videoReferee®	videoReferee® for 8 SDI cameras providing fingertip control browsing, marking, slow motion playback. Display Modes: 4 Live, 1 Live, 4 recorded – Search, 1 recorded – Search/Playback (variable speed), 1 recorded – Zoom search. Includes Control-VR.	✓	✓	✓
12-channel videoReferee®	videoReferee® for 12 SDI cameras providing fingertip control browsing, marking, slow motion playback. Display Modes: 4 Live, 1 Live, 4 recorded – Search, 1 recorded – Search/Playback (variable speed), 1 recorded – Zoom search. Includes Control-VR.	✗	✗	✓
Control ZR Substitution*	Upgraded control console with 51 RGB illuminated push buttons, Jog Shuttle, absolutely new T-Bar, providing up to 1024 values of the lever position and universal connectivity (Ethernet, USB, RS232, RS422).	✓	✓	✓

* Available at ordering