

## videoReferee<sup>®</sup>-4 / 4A / 4G

### Technical characteristics

Parameters	<i>videoReferee<sup>®</sup>-4</i>	<i>videoReferee<sup>®</sup>-4A</i>	<i>videoReferee<sup>®</sup>-4G</i>
<b>Inputs SDI</b>			
HD / SD	16	16	16
3G*	-	-	16
<b>Video Formats</b>			
HD / SD SDI	29.97/59.94Hz based: 1920x1080/59.94i, 1920x1080/29.97PsF, 1280x720/59.94p, 720x480/29.97PsF, 720x480/59.94i 25/50Hz based: 1920x1080/50i, 1920x1080/25PsF, 1280x720/50p, 720x576/25PsF, 720x576/50i Support of 16:9 and 4:3 modes		
3G SDI	—		1920x1080/59.94p, 1920x1080/119.88i, 1920x1080/50p, 1920x1080/100i
<b>Channels (simultaneously)</b>			
HD / SD	16 Recording + 4/1 Search or 1 Playback		16 Recording + 4/1 Search or 1 Playback
3G*	—		16 Recording + 4/1 Search or 1 Playback
<b>Video Standards SDI</b>			
HD / SD	HD video conforms to SMPTE 292M, SMPTE 274 720p video conforms to SMPTE 296M SD video conforms to SMPTE 259M		
3G	—		3G video conforms to SMPTE 424M / SMPTE 425M
<b>Interface monitor</b>	4 (via Display Port)		
<b>Referee output for broadcast**</b>	HD SDI		
<b>Multiviewer</b>	Up to 18 video windows. 2 Layouts		
<b>Gesture control ***</b>	Yes**		
<b>Referee workplaces</b>	1 + 1** (Each additional WP is equipped with vR-Control console)		
<b>Separate engineering workplace</b>	Yes		
<b>Audio Inputs</b>	2 embedded audio channels per video channel (embedders are not included)		

Parameters	videoReferee®-4	videoReferee®-4A	videoReferee®-4G
<b>Audio Outputs</b>	MB audio output / DP		
<b>Internal storage</b>	HDD / SSD		
<b>Storage capacity</b>	16 / 32 TB HDD or 8 / 16 / 32 TB SSD 84 / 168 / 336 hrs. Full HD video		
<b>Scoreboard Interface****</b>	Yes / PiP from any camera		
<b>Compression:</b>			
Recording	I-Frame DCT Based		
Export formats	M2TS; MPEG-4 (*.mp4); H264 (*.mp4); DVD XDCAM 50 (*.mxf) (only for HD)		
<b>Controls</b>	Specialized Jog/Shuttle controllers vR-Control (via RS-232 / RS-485 / USB / Ethernet), Specialized keyboards videoReferee®-Keypad, keyboard, mouse		
<b>Additionally</b>	Ability to network with slomo.tv servers		
<b>Data exchange</b>	1 GbE (Network); Built-in trayless/toolless 3.5" SATA HDD Rack; USB 3.0/eSATA (External HDD Box)		
<b>DMR™ RACK</b>	1		
<b>Control from HQ via Internet</b>	Yes		
<b>Maximum distance of connections</b>	SDI up to 110m; Control up to 150m; DP up to 5m		SDI up to 110m; 3G-SDI up to 90m; Control up to 150m; DP up to 5m
<b>Power Consumption</b>	350 W	120 W	350 W
<b>Power</b>	110V/60Hz or 220V/50Hz Redundant PWR Supply		
<b>Chassis</b>	4U, 19"	2U, 19"	4U, 19"
<b>Dimensions (H x W x L) mm</b>	176.5 x 484 x 591	88 x 482 x 512	176.5 x 484 x 591
<b>Weight Kg</b>	27.7 / 19.5	14	27.7 / 19.5

**Notes:**

\* – 3G SDI Level A, Level B support.

\*\* – optional.

\*\*\* – Touch screen monitor is provided by user. Recommended: Iiyama multi-touch monitor.

\*\*\*\* – Supported: Westerstrand, Nautronic NTPult, Nautronic NAUCON-1000, Bodet, Omega Saturn, Megalux, NatalInfo, Victory, VITA, Araneus-NGLight, ElTablo, Stramatel, Coliseum, CEDR, Favero Console-700.