

## videoReferee®-VHL2G

### Technical characteristics

Parameters	videoReferee®-VHL2G
<b>Inputs 3G/HD SDI</b>	12
<b>Video Formats SDI</b>	
HD/SD	29.97/59.94Hz: 1920x1080/59.94i, 1920x1080/29.97PsF, 1280x720/59.94p, 720x480/29.97PsF, 720x480/59.94i 25/50Hz: 1920x1080/50i, 1920x1080/25PsF, 1280x720/50p, 720x576/25PsF, 720x576/50i Support of 16:9 and 4:3 modes
3G	1920x1080/59.94p, 1920x1080/119.88i, 1920x1080/50p, 1920x1080/100i
<b>Channels (simultaneously)</b>	
HD/SD	12 Recording + 4/1 Search or 1 Playback
3G	12 Recording + 4/1 Search or 1 Playback
<b>Video Standards SDI</b>	
HD/SD	HD video conforms to SMPTE 292M, SMPTE 274 720p video conforms to SMPTE 296M SD video conforms to SMPTE 259M
3G	3G video conforms to SMPTE 424M / SMPTE 425M
<b>Interface monitor</b>	2 (DVI, HDMI™)
<b>Referee output broadcast (optional)</b>	HD SDI
<b>Multiviewer</b>	Up to 14 video windows. 2 Layouts
<b>Referee workplaces</b>	1
<b>Additional Workplace</b>	Optional
<b>Separate engineering workplace</b>	Yes
<b>Gesture control</b>	Optional (Touch screen monitor is provided by user)
<b>Audio Inputs</b>	2 embedded audio channels per video channel (embedders are not included)
<b>Audio Outputs</b>	MB audio output / HDMI™
<b>Internal storage</b>	HDD / SSD
<b>Storage capacity</b>	12 TB 128 hrs. Full HD video
<b>Supported Scoreboard</b>	Westerstrand, Nautronic NTpult, Nautronic NAUCON-1000, Bodet, Omega Saturn, Megalux, NataInfo, Victory, VITA, Araneus-NGLight, ElTablo, Stramatel, Colosseo, CEDR, Favero Console-700 or PiP from any camera
<b>Compression:</b>	
Recording	I-Frame DCT Based
Export formats	M2TS; MPEG-4 (*.mp4); H264 (*.mp4); DVD XDCAM 50 (*.mxf) (only for HD)
<b>Controls</b>	Specialized Jog/Shuttle controllers (via RS-232 /RS-485 / USB / Ethernet); keyboard, mouse
<b>Additionally</b>	Ability to network with slomo.tv servers

Parameters	<b>videoReferee®-VHL2G</b>
<b>Data exchange</b>	1 GbE (Network); Built-in trayless/toolless 3.5" SATA HDD Rack; USB 3.0/eSATA (External HDD Box)
<b>Built-in DMR™ RACK</b>	1
<b>Maximum distance of connections</b>	SDI up to 110m; 3G-SDI up to 90m; Control up to 150m; DVI / HDMI™ up to 5m
<b>Control from HQ via Internet</b>	Yes
<b>Power Consumption</b>	350 W
<b>Power</b>	110V/60Hz or 220V/50Hz
<b>Redundant PWR Supply</b>	Optional
<b>Chassis</b>	4U, 19"
<b>Dimensions (H x W x L) mm</b>	176.5 x 484 x 591
<b>Weight Kg</b>	27.7 / 19.5